



VIN-FP-270/004

climalife®

TEK-MATE DETECTOR



Photo non-contractuelle.

DESCRIPTION

The **Tek-Mate** detector detects all refrigerant types including CFCs, HCFCs and HFCs, HFO based blends such as R-448A, R-450A and HFOs like R-1234yf, R-1234ze and R-1233zd.

An audible and visual alarm will signal the presence of a leak.

Functional and easy to use, the **Tek-Mate Detector** has an automatic calibration sensor and is supplied in a rigid carry case with replacement filters and alkaline « D » batteries.

TECHNICAL DESCRIPTION

- Complies with EN 14624.
- Leak detection by heated diode sensor.
- Stop / start and adjustment by a single switch two sensitivity levels (low - high).
- Visual signal by flashing LED.
- Beep dimmable amplifying is the approach of the leak.
- Automatic calibration.
- LED low battery indicator.
- Flexible probe with foam filter for sensor protection.

SPECIFICATION:

Minimum illumination	≪ 2g/ year
Supply	2 alkaline "D" batteries (1.5 V)
Battery life	≈ 16 hours
Sensor life	≈ 100 hours
Probe length	≈ 380 mm
Range of use	-27°C to +50°C
Weight (with battery)	700g

The information contained in this product sheet is the result of our studies and experience. It is provided in good faith, but should not, under any circumstance, be taken to constitute a guarantee on our part or an assumption of our responsibility. This is particularly the case when third party rights are at stake or in situations where a user of one of our products fails to observe applicable regulations.

For more information visit our website
http://www.climalife.dehon.com/contact_us

