



## FRIONETT® POWER ULTRA



Non contractual photo

### PRESENTATION

Frionett® Power Ultra is a powerful and lightly scented, general-purpose cleaner of all smooth surfaces

This alkaline product is intended for professional cleaning of refrigeration and air-conditioning facilities equipment: heat exchangers (evaporators, condensers), fans, etc.

Disassembly is not required for cleaning. Rinse after 5 minutes of contact.

Its cleansing and degreasing power eliminates dust, grease and other dirt, and in this way makes it possible to optimise the exchangers' heat transfers and restored performance.

There are two versions:

**Frionett® Power Ultra:** concentrated product; must be diluted

**Frionett® Power Ultra RTU:** ready-to-use product

### PROPERTIES

	Frionett® Power Ultra	Frionett® Power Ultra RTU
Appearance	Dark yellow liquid	Light yellow liquid
Density at 20°C (kg/dm <sup>3</sup> )	1.070	1.015
Concentrated pH	12	11.2
Dilution	1 part product to 5 part water	Do not dilute
Solubility in water	Miscible in all proportions	
Wetting ability at 1%	15 seconds	
Degreasing capacity (time from first contact)	8 to 120 seconds	



**Frimonett® Power Ultra**

**climalife®**

## FRIONETT® POWER ULTRA



Non contractual photo

### USAGE

Dilute **Frimonett® Power Ultra** in water, in a ratio of 1 part product to 5 parts water.

After diluting, apply or spray the product directly on the surface to be cleaned or on a damp cloth. Leave it to stand for 5 minutes, and then rinse with water. Repeat as needed.

Packaging: 5 litre container.

### PRECAUTIONS FOR USE

Use in a well-ventilated area.

Use appropriate personal protection equipment.

Refer to the safety data sheet.

## FRIONETT® POWER ULTRA RTU



Non contractual photo

### USAGE

**Frimonett® Power Ultra RTU** is ready to use.

Spray the product directly on the surface to be cleaned, covering the entire surface. Leave it to stand for 5 minutes, and then rinse with water. Repeat as needed.

Packaging: 750 ml trigger spray bottle

### PRECAUTIONS FOR USE

Use in a well-ventilated area.

Use appropriate personal protection equipment.

Refer to the safety data sheet.

These products are an aqueous solution. The facilities' non-waterproof electrical parts must be protected or disconnected from all power sources.

The information contained in this product sheet is the result of our studies and experience. It is provided in good faith, but should not, under any circumstance, be taken to constitute a guarantee on our part or an assumption of our responsibility. This is particularly the case when third party rights are at stake or in situations where a user of one of our products fails to observe applicable regulations.

For more information, visit our website :  
[http://www.climalife.dehon.com/contact\\_us](http://www.climalife.dehon.com/contact_us)

