



Cleaning

NETTOYANT N



Non-contractual photo

INTRODUCTION

Nettoyant N is a ready-to-use liquid product for cleaning pipework that has contained refrigerants, to convert them for use with heat transfer fluid.

This is a non-flammable alkaline detergent without solvent.

Packaging: 20 litre can, 200 litre drum and 1000 litre container.

PHYSIO-CHEMICAL PROPRIETES

Appearance	Green liquid
pH	10
Density at 20°C.....	1.005 g/cm ³
Freezing point.....	-5 °C
Boiling point	> 100°C
Flash point.....	None
Water solubility.....	Fully soluble

USE

Nettoyant N is designed for use in a closed-circuit system.

After recovery of the refrigerant, rinse the circuit with clear water then drain.

Charge the installation with **Nettoyant N** and ensure no air can enter the circuit to avoid foam forming. Circulate the product within the circuit for 15 minutes then drain by the low points. Rinse with clear water until the pH level is approximately 7 (±0.5). Fully drain the circuit and empty the installation.

The installation can then be charged with the selected heat transfer fluid.

Nettoyant N is a non-corrosive product and can be used on everyday materials such as copper, aluminium, steel, stainless steel, brass, iron, rubber, plastic and ceramics .

PRECAUTIONS FOR USE

Refer to the Safety Data Sheet.

The information contained in this product sheet is the result of our studies and experience. It is provided in good faith, but should not, under any circumstance, be taken to constitute a guarantee on our part or an assumption of our responsibility. This is particularly the case when third party rights are at stake or in situations where a user of one of our products fails to observe applicable regulations.



For more information, visit our website :
climalife.com/contact_us



web