



NETTOYANT N



Non contractual picture.

INTRODUCTION

Nettoyant N is a ready-to-use liquid product for cleaning canalisations that have contained refrigerants in order to fill them with heat transfer fluid.

This is a non-flammable alkaline detergent without solvent.

Packaging: 200 litre drum.

PHYSICO-CHEMICAL PROPERTIES

| | |
|------------------------|-------------------------|
| Appearance | green liquid |
| pH | 10 |
| Density at 20°C..... | 1.005 g/cm ³ |
| Freezing point..... | -5 °C |
| Boiling point..... | > 100 °C |
| Flash point..... | none |
| Water solubility | fully soluble |

USE

Nettoyant N is designed for use in a closed circuit system.

After recovery of the refrigerant, rinse the circuit with clear water then drain.

Charge the installation with **Nettoyant N** and ensure there is no air entering the circuit to avoid foam forming. Circulate the product within the circuit for 15 minutes then drain by the low points.

Rinse with clear water until the pH level is approximately 7 (±0.5). Fully drain the circuit and empty the installation.

The installation can then be charged with the selected heat transfer fluid.

Nettoyant N is a non-corrosive product and can be used on everyday materials such as copper, aluminium, steel, stainless steel, brass, iron, rubber, plastic and ceramics.

PRECAUTIONS FOR USE

Refer to the Safety Data Sheet.

The information contained in this product sheet is the result of our studies and experience. It is provided in good faith, but should not, under any circumstance, be taken to constitute a guarantee on our part or an assumption of our responsibility. This is particularly the case when third party rights are at stake or in situations where a user of one of our products fails to observe applicable regulations.

